
## **DI20**

### DRY STEAM GENERATOR WITH DIESEL OIL FIRED STEAM BOILER

- Car washes & Detail shops
- Auto dealerships
- Fleet Companies
- Rent a Car Companies
- Industrial environments in general
- Transportation





2							
	measure units	DI20	DI20 120V	DI20 12V			
product code		085006873	Q80001888	Q80003108			
power supply	V-Hz	230-50	120 V	12 V			
total power	kW	0,4	0,4	0,4			
steam production	g/min	600	600	600			
steam output regulation	type	no	no	no			
working pressure	bar/psi	9/131	9/131	9/131			
steam temperature in boiler	°C/°F	180/356	180/356	180/356			
water output regulation	yes/no	no	no	no			
water output	yes/no	no	no	no			
detergent output	yes/no	no	no	no			
water tank capacity	liter/gallon	27/7,13	27/7,13	optional 30/7,93			
unlimited autonomy	yes/no	yes	yes	yes			
detergent tank capacity	liter/gallon	no	no	no			
machine body material	type	abs	abs	abs			
weight net	kg/lbs	110/243	110/243	110/243			
machine dimension	Ixpxhcm	70x106x102	70x106x102	70x106x102			
packaging dimension	lxpxhcm	80x120x105	80x120x105	80x120x105			
packaging weight	kg/lbs	160/352	160/352	160/352			
packaging box	type	board	board	board			
waste water tank capacity	liter/gallon	-	-	-			
vacuum power	kW	-	-	-			
vacuum	kPA						
vacuum filter	type	-	-	-			
wet & dry	yes/no	-	-	-			
diesel consumption	liter/hour gallon/hour	3,4 0,89	3,4 0,89	3,4 0,89			
diesel tank capacity	liter/gallon	20/5,29	20/5,29	20/5,29			

accessories included two flexible hoses with gun and tip



leader in dry steam technology

The DI20 12V version is powered by a 12V DC source. Ideal for mobile applications (connects to a 12 V DC car battery of at least 100 Ah - not included). Optional 30 liter external water tank.







### General Vapeur S.r.l.

Headquarters: Strada per Castelletto 19/21 - 20080 Albairate (MI) - Italy Phone: +39.02.94981104 • Fax: +39.02.94981134 infoclienti@menikini.com • www.menikini.com • C.S. € 1.800.000





## **DI40**

# DRY STEAM GENERATOR WITH DIESEL OIL FIRED STEAM BOILER

- Car washes & Detail shops
- Auto dealerships
- Fleet Companies
- Rent a Car Companies
- Industrial environments in general
- Transportation



The DI series steam generators are ideal for mobile applications where high power electrical supply is not available.

0 1	117			
	measure units	DI40	DI40 120V	DI40 12V
product code		085006947	Q80001701	Q80003137
power supply	V-Hz	230-50	120 V	12 V
total power	kW	0,4	0,4	0,4
steam production	g/min	600	600	600
steam output regulation	type	no	no	no
working pressure	bar/psi	9/131	9/131	9/131
steam temperature in boiler	°C/°F	180/356	180/356	180/356
water output regulation	yes/no	no	no	no
water output	yes/no	no	no	no
detergent output	yes/no	no	no	no
water tank capacity	liter/gallon	27/7,13	27/7,13	optional 30/7,93
unlimited autonomy	yes/no	yes	yes	yes
detergent tank capacity	liter/gallon	no	no	no
machine body material	type	abs	abs	abs
weight net	kg/lbs	110/243	110/243	110/243
machine dimension	Ixpxhcm	70x106x102	70x106x102	70x106x102
packaging dimension	Ixpxhcm	80x120x105	80x120x105	80x120x105
packaging weight	kg/lbs	160/352	160/352	160/352
packaging box	type	board	board	board
waste water tank capacity	liter/gallon	-	-	-
vacuum power	kW	-	-	-
vacuum	kPA			
vacuum filter	type	-	-	-
wet & dry	yes/no	-	-	-
diesel consumption	liter/hour gallon/hour	3,4 0,89	3,4 0,89	3,4 0,89
diesel tank capacity	liter/gallon	20/5,29	20/5,29	20/5,29

industrial accessories not included for 120 V version see table **C 1** 

#### General Vapeur S.r.l.

Headquarters: Strada per Castelletto 19/21 - 20080 Albairate (MI) - Italy Phone: +39.02.94981104 • Fax: +39.02.94981134 infoclienti@menikini.com • www.menikini.com • C.S. € 1.800.000



leader in dry steam technology



The DI40 12V version is powered by a 12V DC source. Ideal for mobile applications (connects to a 12 V DC car battery of at least 100 Ah - not included).

Optional 30 liter external water tank.







